

## 2312 S

The **TROLL 2312 S** balancer is designed for dynamic balancing of car and light truck wheels in a single measurement cycle. The advantage of the machine is its modern and ergonomic design. The easy calibration system facilitates operation and improves balancing accuracy. The machine features a clear control panel with an LCD display. Parameters are entered manually.



### Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Measuring speed	140 obr/min
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Dimensions	880/1070/1500
Weight	90 kg



## Dostępne kolory



Kolory podstawowe



Kolory na zamówienie

## Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
06.04.008	Stożek 125-145 mm Ø36	
150400049	Stożek 95-132 mm Ø40	
150400043	Stożek 122-174 mm Ø40	



Indeks	Opis	Zdjęcie
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
W-U-5AH	Uchwyt motocyklowy	
PPK-2	Podnośnik koła PPK-1	
T-CĘG-001	Cęgi wulkanizatorskie	

Indeks	Opis	Zdjęcie
CYR-001	Cyrkiel wulkanizatorski	
WT-2065-1	Skrobak do ciężarków klejonych	