

## 24/7

**24/7** is a smaller LCD wheel balancer with automatic measuring arm entering wheel parameters and wheel guidance system directing the wheel to unbalance point. Laser line indicator shows precisely the weight position.

The completely new operating system based on two buttons and a wheel as a selection cursor makes the machine very intuitive to use.

- Automatic positioning lock
- Laser line indicator
- Voice synthesizer
- ALU programmes
- 2 ALU programmes for motorbikes
- programme "hidden weight"
- optimization
- LCD monitor



## Technical Data

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Measuring speed	140 obr/min
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Dimensions	880/1070/1490
Weight	120 kg

## Distinctive features:

---

**Haweke SoftGrip with cylinder 40 mm  
and 3 cones 44-111,5 mm.**



**Anvil.**



**Ergonomic tool tray.**



## Available Colors



Basic Colors




Custom Colors

## Additional Equipment

Index	Description	Photo
DO-5P	Flange plate 5-bolts	
06.04.017.40	Cone 110-125 mm Ø40	
06.04.008.40	Cone 125-145 mm Ø40	
150400043	Cone 122-174 mm Ø40	

Index	Description	Photo
190400018	Distance spacer for shaft Ø40	
W-U-2AH	Motorcycle wheel adaptor	
PPK-1	Wheel lift PPK-1 for wheel balancer	
T-CĘG-001	Wheel Balancing Weight Plier & Hammer Tool	

Index	Description	Photo
CYR-001	Wheel Rim Width Measuring Caliper	
WT-2065-1	Wheel Weight Scraper Tool	