

2312 CLASSIC

2312 CLASSIC is a wheel balancer with an automatic measuring arm to enter wheel parameters and wheel guidance system directing the wheel to unbalance point.

- automatic positioning lock
- automatic measuring arm
- programme ALU
- 2 programmes ALU for motorbike
- optimization
- programme "hidden weight"



Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Measuring speed	140 obr/min
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Dimensions	880/1070/1500
Weight	90 kg

Dostępne kolory



Kolory podstawowe




Kolory na zamówienie

Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
150400049	Stożek 95-132 mm Ø40	
04.04.008.40	Stożek 125-145 mm Ø40	
06.04.009.40	Stożek 145-165 mm Ø40	

Indeks	Opis	Zdjęcie
150400043	Stożek 122-174 mm Ø40	
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
W-U-5AH	Uchwyt motocyklowy	
PPK-2	Podnośnik koła PPK-1	

Indeks	Opis	Zdjęcie
T-CĘG-001	Cęgi wulkanizatorskie	
CYR-001	Cyrkiel wulkanizatorski	
WT-2065-1	Skrobak do ciężarków klejonych	