

SWING

SWING HELPER WDK tyre-changer with 24" table and pneumatically rotating column with a HELPER WDK auxiliary arm.

The special design makes SWING tyre-changer extremely solid, durable and particularly suitable for intensive use. Very strong HELPER WDK auxiliary arm has a specially developed tool that minimizes the risk of tyre damage. Its design and functionality are certified by WDK.

Thanks to its innovative design SWING tyrechanger saves valuable workshop space while maintaining all the functions of modern tyrechangers.

The main column does not tilt backward but is automatically lifted and tilted to the side.



Technical Data

Inside clamping capacity

Max. wheel diameter 1035

Max. wheel width 385 mm (15")

Table rotation speed 6 / 15
Bead-breaker pressure force 15,5 kN
Power of the drive engine 0,75

Weight 370

Electric supply 400V - 3Ph / 50Hz

Pneumatic power supply 8 ÷ 10 bar

Dimensions 1100/1540/2020

Torque: 1000 Nm Number of tire bead breaker positions: 2

Double-acting tire bead breaker: Yes

Removable pedal assembly: Yes

10" - 24"



Advantages:

New mounting head!

New design makes the mounting and dismounting process easier.

The mounting head is lowered using a spring.

Bead breaker

Strong bead breaker operated by doublesided stainless steel cylinder with diameter of 186 mm. Optional plastic covers protect aluminum rims during bead breaking. Adjustable bead breaker stroke significantly improves safety.

Adjustable clamping range

Adjustable clamping range provides an optimal table size and works with aluminum rims up to 24".

Pneumatically locked mounting head

The mounting head is lowered, raised, and locked pneumatically. Plastic covers protect aluminum rims from damage.

Aluminum pedals

Ergonomic aluminium pedals with clear functional symbols. The tubeless inflation side pedal prevents accidental activation.





2-speed system

Table rotation speed is adjusted by the pedal.

Pneumatically rotating arm (column)

The solution allows to save workshop space.

Available Colors



Basic Colors





UNI-TROL Sp. z o.o. ul. Estrady 56 01-932 Warszawa

tel. (22) 817 94 21 22, 817 94 34 35, 834 90 13 14 SPRZEDAŻ wew. 118 i 121, SERWIS wew. 131 i 134 www.unitrol.pl | office@unitrol.pl | serwis@unitrol.pl