

2312 LP

The TROLL 2312 LP wheel balancer is equipped with a modern laser adjustment system that remembers the wheel's parameters during input. After measuring imbalances, it precisely indicates the location for placing the weight. Additionally, the device features an integrated ultrasonic sonar for contactless wheel width measurement.

- Pneumatic wheel mounting clamp
- Auto-guiding to the unbalanced spot
- Automatic adjustment
- ALU programs
- 2 ALU programs for motorcycles
- Optimization
- 3P - hidden weight
- LCD display



Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Measuring speed	140 obr/min
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Dimensions	880/1070/1500
Weight	90 kg

Distinctive features:

Pneumatic clamp.



Anvil.



Ergonomic tool tray.

Dostępne kolory



Kolory podstawowe



Kolory na zamówienie

Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
150 400 049	Stożek 95-132 mm Ø40	
06.04.008.40	Stożek 125-145 mm Ø40	
06.04.009.40	Stożek 145-165 mm Ø40	

Indeks	Opis	Zdjęcie
150400043	Stożek 122-174 mm Ø40	
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
PPK-2	Podnośnik koła PPK-1	
T-CĘG-001	Cęgi wulkanizatorskie	

Indeks	Opis	Zdjęcie
WT-2065-1	Skrobak do ciężarków klejonych	