

MICRO H

Wheel balancer MICRO H is designed for dynamic wheels balancing. Modern and ergonomic design and energy-efficient drive. Simple calibration system facilitates the work and improves the balancing precision. All the features and information are displayed on the legible desktop with LCD display.



Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Electric supply	230V / 50 Hz
Dimensions	450/880/950
Weight	55 kg

Dostępne kolory



Kolory podstawowe



Kolory na zamówienie

Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
06.04.008	Stożek 125-145 mm Ø36	
150400049	Stożek 95-132 mm Ø40	
150400043	Stożek 122-174 mm Ø40	

Indeks	Opis	Zdjęcie
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
W-U-5AH	Uchwyt motocyklowy	
PPK-2	Podnośnik koła PPK-1	
T-CĘG-001	Cęgi wulkanizatorskie	

Indeks	Opis	Zdjęcie
CYR-001	Cyrkiel wulkanizatorski	
WT-2065-1	Skrobak do ciężarków klejonych	