

## MICRO H

**Wheel balancer MICRO H** is designed for dynamic wheels balancing. Modern and ergonomic design and energy-efficient drive. Simple calibration system facilitates the work and improves the balancing precision. All the features and information are displayed on the legible desktop with LCD display.



## Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Electric supply	230V / 50 Hz
Dimensions	450/880/950
Weight	55 kg

## Dostępne kolory



Kolory podstawowe



Kolory na zamówienie



## Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
06.04.008	Stożek 125-145 mm Ø36	
150 400 049	Stożek 95-132 mm Ø40	
150400043	Stożek 122-174 mm Ø40	

Indeks	Opis	Zdjęcie
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
W-U-5AH	Uchwyt motocyklowy	
PPK-2	Podnośnik koła PPK-1	
T-CĘG-001	Cęgi wulkanizatorskie	



Indeks	Opis	Zdjęcie
CYR-001	Cyrkiel wulkanizatorski	
WT-2065-1	Skrobak do ciężarków klejonych	