

## OLA

Simple and solid construction. Side-swinging arm saves space in the car workshop. The machine has two expanding cylinders in the table what significantly increases the clamps strength. Three cylinders for 26 " table.

OPTION - 2-speed motor (7/14 rpm).

Suitable for aluminum rims.



## Technical Data

|                             |                  |
|-----------------------------|------------------|
| Outside clamping capacity   | 10" - 26"        |
| Max. wheel width            | 15"              |
| Max. wheel diameter         | 1070 mm          |
| Bead-breaker pressure force | 2800 kg          |
| Pneumatic supply            | 8 - 10 bar       |
| Table rotation speed        | 7 obr./min.      |
| Electric supply             | 3 x 400V / 50 Hz |
| Motor power                 | 0,75 kW          |
| Weight                      | 180 kg           |
| Wheel clamp                 | Pneumatyczny     |
| Dimensions                  | 800/1520/900     |

## Distinctive features:

---

- strong and solid design
- swing arm for minimum space requirement
- self-centering four jaws turntable
- tyre inflating gun with manometer
- set of jaw protectors for aluminum rims
- head roll guard
- tyre lever
- set of motorcycle adaptors - option
- two-speed motor 7/14 rpm - option

## Available Colors



Basic Colors



Custom Colors

