

2322

2322 is a wheel balancer for dynamic balancing of truck and car wheels in one measurement cycle. Simple and fast calibration system makes work easier and improves balancing accuracy. The machine has legible desktop with LCD display.

2322 Wheel Balancer configuration:

- car and light truck wheel balancing
- truck wheel balancing
- calibration - separate for car and truck wheels
- positioning device / automatic stop at wheel imbalance
- hood
- ALU Function + SPLIT (Hidden Weight) Function - only for car wheels
- digital and LED display indications
- manual offset input
- lift



Technical Data

Rim diameter range:	10" - 30"
Rim width range:	2" - 20"
Maximum wheel weight	200 kg
Balancing accuracy truck wheel	10 g
Balancing accuracy car wheel	1 g
Measuring speed	120 obr/min
Power of the drive engine	150 W
Electric supply	230V / 50 Hz
Pneumatic power supply	8 - 10 bar
Dimensions	1100/1630/1580
Weight	250 kg

Standard equipment for 2322:



Available Colors



Basic Colors



Custom Colors

Additional Equipment

Index	Description	Photo
150400049	Cone 95-132 mm Ø40	
06.04.017.40	Cone 110-125 mm Ø40	
04.04.008.40	Cone 125-145 mm Ø40	
06.04.009.40	Cone 145-165 mm Ø40	

Index	Description	Photo
150400043	Cone 122-174 mm Ø40	
190400018	Distance spacer for shaft Ø40	
T-CĘG-001	Wheel Balancing Weight Plier & Hammer Tool	
WT-2065-1	Wheel Weight Scraper Tool	