

2322

2322 is a wheel balancer for dynamic balancing of truck and car wheels in one measurement cycle. Simple and fast calibration system makes work easier and improves balancing accuracy. The machine has legible desktop with LCD display.

2322 Wheel Balancer configuration:

- car and light truck wheel balancing
- truck wheel balancing
- calibration - separate for car and truck wheels
- positioning device / automatic stop at wheel imbalance
- hood
- ALU Function + SPLIT (Hidden Weight) Function - only for car wheels
- digital and LED display indications
- manual offset input
- lift



Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 20"
Maximum wheel weight	200 kg
Balancing accuracy truck wheel	10 g
Balancing accuracy car wheel	1 g
Measuring speed	120 obr/min
Power of the drive engine	150 W
Electric supply	230V / 50 Hz
Pneumatic power supply	8 - 10 bar
Dimensions	1100/1630/1580
Weight	250 kg

Standard equipment for 2322:



Dostępne kolory






Kolory podstawowe



Kolory na zamówienie

Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
150400049	Stożek 95-132 mm Ø40	
06.04.017.40	Stożek 110-125 mm Ø40	
04.04.008.40	Stożek 125-145 mm Ø40	
06.04.009.40	Stożek 145-165 mm Ø40	

Indeks	Opis	Zdjęcie
150400043	Stożek 122-174 mm Ø40	
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
T-CĘG-001	Cęgi wulkanizatorskie	
WT-2065-1	Skrobak do ciężarków klejonych	