

MONOLITH GEO 3D

MONOLITH GEO 3D is the first Polish diagnostic wheel balancer. In addition to the basic wheel balancing function, the device features an innovative system for measuring runout and tread depth of the balanced wheel. The tread depth and radial run-out of the tire are measured using an additional camera and laser marker.



Dane techniczne

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	80 kg
Balancing accuracy	1 g
Imbalance position indicator accuracy	0.45°
Measuring speed	140 obr/min
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Pneumatic power supply	8 - 10 bar
Dimensions	980/1250/1990
Weight	120 kg

MONOLITH GEO 3D configuration:

- Camera for measuring radial run-out of the tire and tread depth
- Camera for measuring wheel parameters
- Automatic protection hood
- LOT-System (axis for weight positions " at 12 o'clock")
- Pneumatic quick clamp
- Pneumatic brake at unbalance position
- Calibration
- Voice synthesizer
- Laser adjuster
- Alu programmes
- Automatic positioning lock
- Contactless wheel parameters measurement
- Optimization
- USG rim width measurement
- Programme 3P - "hidden weight"
- Touchscreen LED monitor
- Print to file
- Operator's memory
- Automatic diameter, width and offset measurement
- Unbalance recalculating

Distinctive features:

The clamping mechanism is operated using a convenient foot pedal.





The measurement results are displayed in a clear menu that helps the user verify the tire.

The balancer is equipped with a patented system of automatic wheel parameters input based on real camera image. The laser pointer defines more precisely the correction point and shows the exact position for adhesive weights application.



Modern pneumatic quick-clamp significantly shortens the wheel mounting time and eliminates the risk of eccentric wheel mounting. Clamp mechanism is controlled by ergonomic pedal.

MONOLITH series is an ultra-modern balancing machine with even more accurate indication of the correction place. The laser beam sets axis "at 12 o'clock" eliminating the risk of mistakes in placing clip-on weights.



United States of America



(12) **United States Patent**
Roguski et al.

(10) **Patent No.:** US 10,281,355 B2
(45) **Date of Patent:** May 7, 2019

(54) **METHOD AND SYSTEM FOR THE OPTICAL DETERMINATION OF CORRECTION PLANES IN ROTATING ELEMENTS**

FOREIGN PATENT DOCUMENTS

EP 0724144 7/1996
EP 1398611 3/2004
WO 98/10261 3/1998

(71) Applicant: **UNIT S.C. Wieslaw Roguski, Jan Tworek, Zaborow (PL)**

(72) Inventors: **Wieslaw Albin Roguski, Lomianki (PL); Wojciech Wieslaw Roguski, Lomianki (PL); Jan Tworek, Warsaw (PL)**

OTHER PUBLICATIONS

EP Search Report for EP16185127, completed Jan. 17, 2017.
PPO Search Report for P413757, completed Sep. 5, 2016.

(73) Assignee: **UNIT S.C. WIESLAW ROGUSKI, JAN TWOREK, Warsaw (PL)**

Primary Examiner—Walter L Lindsay, Jr.
Assistant Examiner—Philipmarcus T Fadul
(74) *Attorney, Agent, or Firm*—Barnes & Thornburg LLP

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 279 days.

(57) **ABSTRACT**

The subject matter of the present invention relates to a system for the optical determination of correction planes in rotating elements, used in the process of balancing, in particular in diagnostic devices equipped with a system which has at least one video camera (K), at least one line projector (RL), a monitor screen (M) and a computer (P) which controls individual component elements of the system, wherein the video camera (K) cooperates with the line projector (RL) while projecting a view of the rotating element (EW) on the monitor screen (M) together with an image of a line (L) projected by means of the line projector (RL).

The subject matter of the present invention also relates to a method for determining correction planes which consists in defining an area of measurement space; is defined on the basis of a virtual rotating element (EW) by placing a rotating element (EW) on the shaft of a diagnostic device (PM) onto which line (L) is projected by means of a line projector (RL), and subsequently an image of the rotating element (EW) is transmitted by means of the video camera (K) to the monitor screen (M) together with an image of the projected line (L), and thus the angles of the lines obtained which forms a change in the values of the radius r_1 from the axis of the shaft of the diagnostic device (PM) and the angle of distance d_1 of the rotating element (EW) from the diagnostic device (PM) in the defined area of measurement space.

(21) Appl. No.: 15/242,957

(22) Filed: Aug. 22, 2016

(65) Prior Publication Data
US 2017/005940 A1 Mar. 2, 2017

(51) Int. Cl.
G01M 1/28 (2006.01)
G01M 1/16 (2006.01)

(Continued)


(52) U.S. Cl.
CPC G01M 1/16 (2013.01); G01M 1/225 (2013.01); G01M 1/28 (2013.01); G01M 1/3081 (2013.01); G01M 7/181 (2013.01)

(58) Field of Classification Search
CPC G01M 1/16 (Continued)

(56) References Cited

U.S. PATENT DOCUMENTS
5,827,964 A 10/1998 Douine et al.
6,484,574 B1 11/2002 Douglas et al.
(Continued)

6 Claims, 6 Drawing Sheets



Andreas Jansen
DIRECTOR OF THE UNITED STATES PATENT AND TRADEMARK OFFICE

The device was awarded a gold medal at the TTM 2024 trade fair in Poznań.



Dostępne kolory




Kolory podstawowe



Kolory na zamówienie

Wyposażenie dodatkowe

Indeks	Opis	Zdjęcie
DO-5P	Docisk palcowy 5-bolcowy	
06.04.017.40	Stożek 110-125 mm Ø40	
04.04.008.40	Stożek 125-145 mm Ø40	
06.04.009.40	Stożek 145-165 mm Ø40	

Indeks	Opis	Zdjęcie
150400043	Stożek 122-174 mm Ø40	
190400018	Pierścień dystansowy do stożków dostawczych Ø40	
PPK-2	Podnośnik koła PPK-1	
T-CĘG-001	Cęgi wulkanizatorskie	

Indeks	Opis	Zdjęcie
WT-2065-1	Skrobak do ciężarków klejonych	