

MANAGER



Dane techniczne

Felgenaussenspannung	12" - 24"
Spannbereich innen	14" - 26"
Max. Radbreite	15"
Max. Raddurchmesser	1150 mm
Abdruckerkraft	3500 kg
Luftversorgung	8 - 10 bar
Drehgeschwindigkeit	8 / 16 obr./min.
Spannungsversorgung	3 x 400V / 50 Hz
Motorleistung	1,3 kW / 1,8 kW
Gewicht	380 kg
Radhalter	Pneumatyczny
Maße	1430/860/1550

Automatic tyre-changer MANAGER 12 " - 26"

For rims from 12 " to 26"
Automatic column tilting
Helper PLUS for high performance tyres
Two speeds (8-16 rpm)
Automatic bead-breaker
Additional shelves with inflator
Automatic Leverless finger - (optional)
Inflator for tubeless tyres TI - (optional)
New steering pedal system
Modern look
New locking system
Working pressure 8-10 Bar



Automatically tilting column Automatic bead-breaker

Assistant PLUS

Additional shelves with inflator

Two speeds (8-16 rpm) Inflator TI for tubeless tyres

Automatic Leverless finger Reinforced structure

UNI-TROL Sp. z o.o.
ul. Estrady 56
01-932 Warszawa

tel. (22) 817 94 21 22, 817 94 34 35, 834 90 13 14
SPRZEDAŻ wew. 118 i 121, SERWIS wew. 131 i 134
www.unitrol.pl | office@unitrol.pl | serwis@unitrol.pl

